

# ALU 100 NEO PRO Glass Synchron



**NEW:** can also be combined with a damper for perfect closing every time.

The ALU 100 NEO PRO - Glass Synchron Set is a maintenance and wear-free sliding door system with a particularly compact design. The high-quality components create a dramatic effect with little assembly effort. This makes it possible to open and close larger passages in an appealing, quick and convenient way.



Hanger  
RX100A, 4 pieces



Glass clamp  
GLM 274087M, 4 pieces



Stopper  
SX 100A, 4 pieces



Floor guide  
T-Guide Glas, 2 pieces



Retaining spring  
SX-H, 2 pieces



Toothed Belt  
05M, 10m



Deflection Unit  
2 pieces



Catcher set  
281001-Sync



Tool

System-Set

PRO100G-Sync

**Optional:** Cover panel set for Glass Clamp GLM, including side cover

1200 mm, anodized aluminium, EV1 silver

B272087-1200-14

12000 mm, anodized aluminium, EV1 silver

B272087-2000-14

1200 mm, anodized aluminium, C31 stainless-steel-look

B272087C-1200-14

2000 mm, anodized aluminium, C31 stainless-steel-look

B272087C-2000-14

The optional cover kit allows for a continuous aluminium cladding of the glass clamps.

Please note: The snap-on covers are only required if the clamps are visible after installation.

## Technical Notes

**Maximum Door Weight** 2 x 100 kg

**Height** 73 ± 2 mm

**Glass Thickness** 8 und 10 mm (12 mm upon request)

**Minimum Door Width** 500 mm

**Maximum Door Width** 1250 mm

## Classification according to DIN EN 1527

Use Category	Durability	Door Weight	Fire Resistance	Safety	Corrosion Resistance	Security	Door Type	Initial Friction
-	6	2	0	-	0	-	1	3

