

ALU 100 NEO PRO Telescopic 3-Part

NEW: can be combined with an intake damper for perfect closing action.



Hanger
RX100A, 4 pieces



Flange
8069, 4 pieces



Adjustable stopper
SX 100H, 2 pieces



Toothed belt
05M, 6 m



Guide roller
for side-by-side doors,
15 mm, 204129,
2 pieces



Guide roller
on flange, 15 mm,
18129



Deflection unit 1
203009-U1, 2 pieces



Deflection unit 3
203009-U3



Deflection unit 1
203009-U2



Catcher 1
203009-1



Catcher 2
203009-2, 2 pieces



Catcher 3
203089-M3

System-Set

PRO100T3

ALU 100 NEO PRO Telescopic 4-Part available upon request.

Technical Notes

Maximum Door Weight	3-flg.= 3 x 65 kg
Height	70 ± 3 mm
Door Thickness	35 - 50 mm
Minimum Door Width	600 mm
Maximum Door Width	1200 mm

Classification according to DIN EN 1527

Use Category	Durability	Door Weight	Fire Resistance	Safety	Corrosion Resistance	Security	Door Type	Initial Friction
-	6	2	0	-	0	-	1	3

Optional Guide rail
for 3-part Telescopic:



$$T = \frac{D}{2} - 3,5$$

